

## E-Plex Bridging Module



### Introduction

The E-Plex 387EBM Bridge Module is capable of bridging between two independent E-Plex systems, and provides a galvanically isolated link between them, allowing 128 bits of information to be transferred in each direction.

### Key Features

- Dual EP3 Connections
- 128bit bi-directional interface
- Galvanic isolation
- Simple installation
- Easy to set-up within E-Logic

### Electrical Specifications

Eplex LEN: nominal 4  
External power voltage: 6VDC (min), 12/24VDC (nom), 32VDC (max)  
Current: 20mA (min) – 30mA (max)

### Ordering codes

Description	Ordering Code
387EBM Bridging Module	EP3-CLOCK-BRIDGE-387EBM



52 – 54 Riverside, Sir Thomas Longley Road, Medway City Estate, Rochester, Kent ME2 4DP  
tel: +44 (0)1634 711622 fax: +44 (0)1634 290773

email: [sales@e-plex.co](mailto:sales@e-plex.co)  
web: [www.e-plex.co](http://www.e-plex.co)

Important Notice: E-Plex Ltd. (E-Plex) reserves the right to make changes to or discontinue any product or service identified in this publication without notice. E-Plex advises its customers to obtain the latest version of the relevant information to verify, before placing any orders, that the information being relied upon is current. E-Plex assumes no responsibility for infringement of patents or rights of others based on E-Plex applications assistance or product specifications since E-Plex does not possess full access concerning the use or application of customers' products. E-Plex also assumes no responsibility for customers' product designs.